

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**

```

// sitepage.cpp

#include "stdafx.h"
#include "object.h"
#include "d/cookie/db.h"
#include "d/cookie/istutil.h"
#include "d/cookie/cookie.h"

void message(const char *);

SitePage::SitePage()
{
    id = 0;
    siteid = 0;
    categorized = FALSE;

    void SitePage::loadCategories()
    {
        DWORD interested;
        Cursor ci;
        cbindSQL_C_LONG, interested, siteid(interested);
        char sql[1024] = "select interested_id from page_categories where page_id=";
        addvalue(buf, id, FALSE);
        strcat(sql, " union all select interested_id from site_categories where site_id=");
        addvalue(buf, siteid, FALSE);
        strcat(sql, " ");
        while (c.fetchNext()) {
            categories.Add(interested);
        }
    }

    extern BOOL defaultMode;

    SitePage::loadPage(Database db, const char *from, const char *requestHdr);

    // from key format: sitekey/docname
    if (from == 0)
        return 0;

    if (strlen(from) < 1) // " "
        return 0;

    if (from == 0)
        return 0;

    const char *q = strchr(from, '/');
    if (q == 0 || strlen(from) < 15)
        return 0;

    CString key;

    // truncate a unique number from the end of the key
    const char *lastSlash = strchr(q, '/');
    if (lastSlash != lastdigit(lastSlash))
        key = CString(from, lastSlash - from);
    else
        key = from;

    if (key.GetLength() > 64)
        key = key.Left(64); // truncate to column width

    SitePage *p = new SitePage;

```

DC 069516

HIGHLY
CONFIDENTIAL

```

// Didn't find the page. Add page if site is correct.
CString sitekey(from, q - from);
int approved = 0;
Cursor ci(db);
cbindSQL_C_LONG, approved, siteid(p-siteid);
c.execute(buf, "select id,approved from sites where keyname=");
sql = sitekey + " ";
c.execute(buf);
if (c.fetchNext()) {
    if (approved == 0) {
        message(CString("unapproved site: ") + from);
    }
    else {
        p->addIdb, key;
    }
}
else {
    delete p;
    p = 0;
    if (defaultMode)
        message(CString("unknown site: ") + from);
}

return p;
}

void SitePage::add(Database db, const char *keyname)
{
    char buf[1024] = "insert sitepages(junk, keyname, site, categorized) values('";
    addvalue(buf, keyname);
    addvalue(buf, (int) siteid);
    addvalue(buf, (int) categorized, FALSE);
    strcat(buf, "')";
    if (db.execute(buf) != 1) {
        TRACE("error adding sitekey\n");
        CString a = "sql: ";
        a += buf;
        ASSERT(FALSE);
        TRACE(a);
        message(a);
    }
}

Cursor ci(db);
id = 0;
cbindSQL_C_LONG, id, 0;
strcpy(buf, "select id from sitepages where keyname=");
addvalue(buf, keyname, FALSE);
c.execute(buf);
if (c.fetchNext()) {
}
}

```

```

AD.CPP
//
// ad.cpp
//
#include "stdat.h"
#include "strstream.h"
#include "fstream.h"
#include "unistd.h"
#include "objects.h"
#include "d/toolkit/af.utli.h"
#include "d/toolkit/db.h"
#include "d/toolkit/dbut.h"
#include "d/derive/enlderive.h"
#include "d/newder/enl.h"
#include "newderau.h"

const CString gRootDir = "c:\\lan\\ade\\";
if (defined_DEV)
int main() { return ad.GetSize(); }
endif
extern Database (ofmain);
//.....
// Ad
Ad::Ad()
{
delete[] locations;
delete[] sicCodes;
}

```

```

Ad::Ad(const Ad &ad)
{
startted.started;
totad.id, filename(ad.filename), jumptolad.jumptol,
type(ad.type), ofad.of, browser(ad.browser),
domaintype(ad.domaintype), leptad.lept,
maximpressions(ad.maximpressions), nshown(ad.nshown),
nlocations(ad.nlocations), nsicCodes(ad.nsicCodes),
frequency(ad.frequency), images(ad.images),
series(ad.series), starttime(ad.starttime), endtime(ad.endtime),
allod.all, flag(ad.flag),
hoursOfDay(ad.hoursOfDay), dayOfWeek(ad.dayOfWeek),
employees(ad.employees), salesVolume(ad.salesVolume),
gender(ad.gender), address(ad.address),
maxAmount(ad.maxAmount), sponumber(ad.sponumber),
activated(ad.activated), includesites(ad.includesites),
includePages(ad.includePages), approved(ad.approved),
nJumps(ad.nJumps)
}
}

```

```

Ad::Ad(const CString filename)
{
stripSpaces(filename);
stripSpaces(jumptol);
locations = 0;
if (nLocations) {
locations = new RegionInLocations();
for (int i = 0; i < nLocations; i++) {
locations[i] = ad.locations[i];
}
}
}

```

DC 069517

HIGHLY
CONFIDENTIAL

```

{
sicCodes = 0;
if (nsicCodes) {
sicCodes = new sicCodes(nsicCodes);
for (int i = 0; i < nsicCodes; i++) {
sicCodes[i] = ad.sicCodes[i];
}
}
}

```

```

void Ad::calcS()
{
if (maximpressions == 0)
return;
}

```

```

AD.CPP
time_t t;
DWORD totalSpan = endTime - startTime;
if (totalSpan == 0)
totalSpan = 1;
DWORD span = time(t) - startTime; if (span == 0) span = 1;

si =
(dwOrd) ((double) nshown /
(double) span / totalSpan) /
maximpressions * 1000;

void Ad::show()
{
if (nshown == 0) {
// if (nshown == 0) {
// // update si
// // calcS();
// }
}
Ad::Ad()
{
daysOfWeek = 0x7f;
started = FALSE;
flags = Production | SpreadEvenly;
si = 1000;
sicCodes = 0;
nsicCodes = 0;
frequency = 0;
imageSeries = FALSE;
id = 0;
maximpressions = 0;
nshown = 0;
nJumps = 0;
type = Normal;
nLocations = 0;
incontinua = 0;
gender = 0;
maxAmount = 0;
active = 0;
approved = 0;
includesites = 0;
starttime = 0;
endtime = 0;
os = DefaultMask;
browser = DefaultMask;
domaintype = DefaultMask;
lap = DefaultMask;
hoursOfDay = 0x7f;
employees = DefaultMask;
salesVolume = DefaultMask;
gender = DefaultMask;
seriesNext = 0;
}

CString Ad::getFileName()
{
if (imageSeries || seriesNext == 1)
return filename;

char buf[256];
sprintf(buf, "%ld.gif", (const char *) filename.Left(filename.GetLength() - 4), seriesNext);
return buf;
}

CString Ad::fullFilename()
{
return gRootDir + getFileName();
}

if (defined_ADSVP)

```

```

// users.cpp
#include "data.h"
#include "objects.h"
#include "d/cookie/db.h"
#include "d/cookie/af_util.h"
#include "d/cookie/dbutil.h"

/* Implementation for hash tables */
User User::lookupUserByDID(DWORD userID)
{
    return u;
}

User u = new User;

User User::lookupUserByIPAddress(DWORD ip)
{
    DWORD userID = networkNodeTable->getUserID(ip, FALSE);
    if (userID == 0) {
        // Try to get domain info at least. Note: If user is uniquely
        // identifiable, derive data process will create a record for the
        // user as soon as it gets a chance.
        userID = networkNodeTable->getUserID(justNetworkNumber(ip), TRUE);
    }
    if (userID) {
        return lookupUserByDID(userID);
    }
    return 0;
}

class UserCursor : public Cursor
{
public:
    UserCursor(Database db, User *u) : Cursor(db),
        u(u) {}

    // Just gets field that aren't derivable from request header
    void minimalBind()
    {
        bind( SQL_C_LONG, u->scripted, sizeof(BOOL) );
        bind( SQL_C_LONG, u->cookie, sizeof(BOOL) );
    }

    User *u;
};

void User::lookupAuxiliaryInfo(Database db)
{
    if (userID == 0) {
        return;
    }
    Cursor c(db);
    char sql[256];
    sprintf(sql, "select email from users where id=%ld", userID);
    c.bindEmailAddr();
    c.execute();
    c.fetch();
    c.commit();
}

User User::lookupUserByDID(Database db, DWORD userID, BOOL *found)
{
    User *u = new User;
    UserCursor c(db, u);
    c.minimalBind();
    char sql[256];
    sprintf(sql, "select fp_tried,has_cookie from users where id=%ld", userID);
    if (found != 0)
        c.execute();
    c.execute();
}

```

DC 069514
HIGHLY
CONFIDENTIAL

```

    if (c.timeOut() ) {
        *timeOut = TRUE;
        delete u; u = 0;
    }
    else if ( c.fetchNext() ) {
        u.userID = userID;
    } else {
        delete u;
        u = 0;
    }
}

return u;
}

User User::lookupByAddress(Database db, Word ip, bool *timeOut)
{
    User *u = new User;
    UserCursor c(db, u);
    c.bind(SQL_C_LONG, &u.userID, 4);
    char a[128];
    sprintf(a, "select ip,ried,hasCookie,id from users where ip=%s",
        ip.c_str());
    if (timeOut != 0)
        c.setTimeOut(1);
    c.exec(a);
    if (c.timeOut() ) {
        *timeOut = TRUE;
        delete u;
        u = 0;
    }
    else if ( c.fetchNext() ) {
        delete u;
        u = 0;
    }
    return u;
}

void User::updateFPried(Database db)
{
    if (tempUserObject() ) {
        ASSERT(FALSE);
        return;
    }
    char buf[256];
    sprintf(buf, "update users set fp_ried=id where id=%ld",
        fpried);
    db.exec(buf);
    db.commit();
}

void User::makePermanent(Database db)
{
    if (tempUserObject() )
        return;
    ASSERT(name.isEmpty() || title.isEmpty() || emailAddr.isEmpty());
    char buf[1024];
    sprintf(buf, "insert users (fp_browser,ver1,ver2,os,domain_type,ip,proxy,ip_networkdesc,fp_ried,hasCookie) values (%s)",
        addValue(buf, fp_browser);
    addValue(buf, ip);
    addValue(buf, browser);
    addValue(buf, ver1);
    addValue(buf, ver2);
    addValue(buf, os);
    addValue(buf, domainType);
    addValue(buf, proxy);
    addValue(buf, fp_ried);
    addValue(buf, hasCookie);
    addValue(buf, ipNetworkDescription);
    addValue(buf, fpried);
}

```

33-Dec-1995 16:53

users.cpp

```

addBool(buf, hasCookie, FALSE);
strcpy(buf, "-");
if (db.doinsert(buf) == 1) {
    Cursor c(db);
    c.find(SOL_C_LONG, userID, 4);
    strcpy(buf, "select max(id) from users where ip=");
    addInValue(buf, ip, FALSE);
    c.exec(buf);
    c.fetchNext();
    ASSERT(userID != 0);
}
db.commit();
}

```

HIGHLY
CONFIDENTIAL

DC 069515


```

if defined(_IAP)
    IAPRequest gr(c, v, r, from);
    tell defined_ADQ(n)
        GetRequest gr(c, v, r, from);
    else
        MgmtRequest gr(c, v, r, from);
    sendit
        gr.service();
}

Listener *listener = 0;

static DWORD id = GetTickCount();
static DWORD id2 = GetTickCount();

while (1) {
    socketaddr_in from;
    Connection *c = listener->waitForConnection(&from);
    if (c) {
        Crit c(fast);
        int n = nThread;
        if (n > maxThreads)
            maxThreads = n;
        serviceRequest(c, from);
        delete c;
    }
    Crit c(fast);
    nThread--;
    if (nThread == 0) {
        // idle
        qpurge();
    }
}

if defined(_IAP)
    sendit
        return 0;
}

BOOL startServer()
{
    if defined_ADQ(n)
        if (IsOpenTablet()) {
            AfxMessageBox("Error opening tablet");
            return FALSE;
        }
    if (InitWinsock()) {
        return FALSE;
    }
    mapStateInit();
    InitCountryTimezoneTable();
    sendit
    if 0
    {
        // TCP
        Connection c;
        if (c.connect("www.microsoft.com", 80)) {
            c.write("GET /sdf HTTP/1.0\r\n\r\n", 32);
            while (1) {
                char buf[256];
                int n = c.read(buf, 255);
            }
        }
    }
}

```

HIGHLY
CONFIDENTIAL

DC 069513

```

if (n) {
    buf[n] = 0;
    TRACE("15", buf);
}
else
    break;
}
return TRUE;
}
endif

if defined(_PORT)
    int port = _PORT;
    else
        int port = 80;
    sendit
        listener = new Listener(port);
        if (listener->start()) {
            if defined_ADQ(n)
                errLog.open("c:/lan/errlog.txt",
                    ios::out | ios::app,
                    filebuf::sh_read);
                ASSERT(errLog.is_open());
                errLog << "-----ad server started\n"; errLog.flush();
            }
        }
        for (int i = 0; i < listenerThreads; i++) {
            Sleep(100); // [dml] this is a test; sometimes it doesn't listen right, just a hunch
            AfxBeginThread(listenerThread, 0);
        }
    else
        ASSERT(FALSE);
    return TRUE;
}
endif

```



```

char sql[512] = "select sicode from placement_sics where ad_id=";
addValue(sql, ad_id, FALSE);
c.execute();
sicode = 0;
while( c.fetchNext() ) {
    *tripspace(sql);
    if( s == 0 ) {
        // to do: count the # of sics first, and allocate that number
        // to do: rather than 50
        s = new sicode[n];
        ad.sicCodes = s;
    }
    *s = s;
    if( ++ad.nsicCodes == n ) {
        ASSERT( !c.fetchNext() );
        break;
    }
    *s++;
}

// load regional
for( i = 0; i < ad.GetSize(); i++ ) {
    region[i] = 0;
    ad.ad = *ad.GetSizeAt(i);
    if( !ad.isTargeted() )
        continue;

    int n = 0;
    Cursor c;
    c.bind(SQL_C_LONG, ln, sizeof(n));
    char sql[512] = "select count(*) from placement_locations where ad_id=";
    addValue(sql, ad_id, FALSE);
    c.execute();
    if( !c.fetchNext() )
        continue;
    if( n == 0 )
        continue;
    if( n > 100 )
        message("100 locations targeted");
}

Cursor c;
WORD country;
CString state, sip;
int areaCode;
c.bind(SQL_C_LONG, scountry, sizeof(country));
c.bind(state);
c.bind(sip);
c.bind(SQL_C_LONG, areaCode, sizeof(areaCode));
char sql[512] = "select country, state, sipcode, areacode from placement_locations where ad=";
addValue(sql, ad_id, FALSE);
c.execute();
areaCode = 0;
while( c.fetchNext() ) {
    if( i == 0 ) {
        *s = new Region(n);
        ad.locations = i;
    }
    i--country = country;
    i--state = state;
    i--sipCode = sip;
    i--areaCode = areaCode;
    if( ++ad.nLocations == n ) {
        ASSERT( !c.fetchNext() );
        break;
    }
    i--;
    areaCode = 0;
}

if( !main.commit() )

```

HIGHLY
CONFIDENTIAL

DC 069511

```

if( !ad.GetSize() == 0 is (orTargeting) ) {
    // db connection down, use some default ada
    makeDefaultAda(ada);
}

if( defaultAd == 0 ) {
    TPAGE("no default ad\n");
    message("no default ad");
}

return ada.GetSize() == 0 is defaultAd == 0;

```



```

static void makeDefaultAds (AdArray& ads)
{
    ifstream defads ("c:\\lan\\default_ads.txt");
    if (!defads.is_open()) {
        ASSERT(FALSE);
        return;
    }
    message<db connection failed, using default_ads.txt>;
    defaultAdMode = TRUE;
    while (1) {
        char fn(128);
        char jumpTo(128);
        *fn = 0;
        defads >> fn >> jumpTo;
        if (*fn == 0)
            break;
        Adt ad = * (new Ad);
        defaultAd = *ad;
        time_t now;
        ad.startTime = time(&now) - 60 * 60 * 24 * 15;
        ad.endTime = now + 60 * 60 * 24 * 15;
        ad.fileName = fn;
        ad.jumpTo = jumpTo;
        ads.Add(ad);
    }

    BOOL loadDefaultAdArray ads;
    DWORD advertiseID;
    BOOL fortargeting; // 0=all
    // If fortargeting, update Ad::targetSite to reflect
    // site exclusions
    BOOL activeOnly; // active only
    BOOL includeExpired; // include where enddate has past or where all delivered
    // (for management and reporting...)
    BOOL newestFirst; // order from newest to oldest
    DWORD approveSiteID // exclude ads the specified site has approved

    // calc time zone adjustment
    time_t = CTime::GetCurrentTime();
    tm gmt, local;
    t.GetGmt(&gmt);
    t.GetLocal(&local);
    if (local.tm_hour > gmt.tm_hour)
        gmt.tm_hour += 24;
    utof = (gmt.tm_hour - local.tm_hour) * 60 * 60;

    ads.SetSiteID( 64);

    DWORD active = 1;
    GetConfigValue("Active", active);
    AdCursor ad;
    char eq(1000);
    *select id, type, os, browser, domainType, lap, filename, jumpTo, frequency, image, series, \
max_impressions, n_how, datediff(, '1/1/70', start_time), datediff(, '1/1/70', end_time), \
flags, hours_of_day, day_of_week, employee, sales, active, description, max_amount, po_number, \
approved, n_jump from placements';
    BOOL where = FALSE;

    if (!includeExpired) {
        strcat(eq, " where (max_impressions=0 or n_shown=max_impressions) and \
(end_time=null or end_time=getdate())");
        where = TRUE;
    }

    if (activeOnly) {
        if (where) {
            strcat(eq, " and");
        } else {
            strcat(eq, " where");
        }
    }
}

```

HIGHLY

```

        where = TRUE;
        strcat(eq, " where");
    }
    strcat(eq, " active=");
    addValue(eq, active, FALSE);
}

if (advertiseID) {
    if (where) {
        strcat(eq, " and");
    } else {
        where = TRUE;
        strcat(eq, " where");
    }
    strcat(eq, " advertise=");
    addValue(eq, advertiseID, FALSE);
}

if (approveSiteID) {
    if (where) {
        strcat(eq, " and");
    } else {
        where = TRUE;
        strcat(eq, " where");
    }
    strcat(eq, " not exists (select * from approved where site_id=");
    addValue(eq, approveSiteID, FALSE);
    strcat(eq, " and ad_id=");
}

if (newestFirst) {
    strcat(eq, " order by id desc");
}

rs->exec(eq);

while (1) {
    // defaults in case null
    rs.ad.flags = 0;

    if (rs.fetchNext())
        break;

    // If for debug, don't load. You can make this test a registry
    // setting if you like so that you can load debug records, or
    // add a cmd line setting.
    if (rs.ad.isProduction())
        continue;

    if (rs.isNull(112)) {
        time_t now;
        rs.ad.startTime = time(&now);
        rs.ad.endTime = rs.ad.startTime + 60 * 60 * 24 * 30;
    }
    else {
        localTOUCT(rs.ad.startTime);
        localTOUCT(rs.ad.endTime);
    }
    if (rs.isNull(112)) {
        // ad server needs fake times for now...
        if (fortargeting) {
            time_t now;
            rs.ad.startTime = time(&now) - 60 * 60 * 24 * 15;
            rs.ad.endTime = now + 60 * 60 * 24 * 15;
        }
        else {
            rs.ad.startTime = rs.ad.endTime = 0;
        }
    }
    else {
        localTOUCT(rs.ad.startTime);
        localTOUCT(rs.ad.endTime);
    }
}

```

```

    {
        strcat(buf, "%m/%d/%y", gettime(&startime));
        addvalue(buf, startime);
    }
    else
    {
        strcat(buf, "(null)");
    }
    strcat(buf, "end_time");
    if (sendtime)
    {
        strcat(buf, "%m/%d/%y", gettime(&sendtime));
        addvalue(buf, startime, FALSE);
    }
    else
    {
        strcat(buf, "(null)");
    }
    strcat(buf, "where_id");
    addvalue(buf, id, FALSE);
    if (!ifmain_exact(buf) || 1)
    {
        ASSERT(0);
        return FALSE;
    }
    return AddPlacementTable(id);
}

return FALSE;

}

return AddPlacementTable(DWORD adid)

char buf(1024);
BOOL bnc = TRUE;

while (TRUE)
{
    // Now save the locations to the "placement_locations" table
    // for (int nloop = 0; nloop < nLocations; nloop++)
    {
        strcpy(buf, "insert placement_locations");
        if (!locations[nloop].country)
            strcat(buf, "country");
        if (!locations[nloop].state.isEmpty())
            strcat(buf, "state");
        if (!locations[nloop].zipcode.isEmpty())
            strcat(buf, "zipcode");
        if (!locations[nloop].areacode)
            strcat(buf, "areacode");
        strcat(buf, "ad_id values");
        if (!locations[nloop].country)
            addvalue(buf, locations[nloop].country);
        if (!locations[nloop].state.isEmpty())
            addvalue(buf, locations[nloop].state);
        if (!locations[nloop].zipcode.isEmpty())
            addvalue(buf, locations[nloop].zipcode);
        if (!locations[nloop].areacode)
            addvalue(buf, locations[nloop].areacode);
        addvalue(buf, adid, FALSE);
        strcat(buf, ");");
        if (!ifmain_exact(buf) || 1)
        {
            ASSERT(0);
        }
    }
}

```

DC 069519

CONFIDENTIAL
HIGHLY

```

    bnc = FALSE;
    break;
}

// Now save the sites to the "placement_sites" table
// for (int nloop = 0; nloop < nSites; nloop++)
{
    printf(buf, "insert placement_sites(ad_id,site_id,include) values(id,'%s',",
        adid, siteCode[nloop].areact());
    if (!ifmain_exact(buf) || 1)
    {
        ASSERT(0);
        bnc = FALSE;
        break;
    }
}

// Now save the site categories to the placement_sitecat table
// POSITION pos = siteCategories.GetStartPosition();
// DWORD dwInterestID;
// while (pos)
{
    siteCategories.GetNextAssoc(pos, dwInterestID, bnc);
    printf(buf, "insert placement_sitecat(ad_id,interest_id) values(id,'%s',",
        adid, dwInterestID);
    if (!ifmain_exact(buf) || 1)
    {
        ASSERT(0);
        bnc = FALSE;
        break;
    }
}

// Now save the user interests to the placement_interest table
// pos = interests.GetStartPosition();
// while (pos)
{
    interests.GetNextAssoc(pos, dwInterestID, bnc);
    printf(buf, "insert placement_interest(ad_id,interest_id) values(id,'%s',",
        adid, dwInterestID);
    if (!ifmain_exact(buf) || 1)
    {
        ASSERT(0);
        bnc = FALSE;
        break;
    }
}

// Now save site include-exclude list in the placement_sites table
// pos = targetSites.GetStartPosition();
// DWORD dwSiteID;
// while (pos)
{
    targetSites.GetNextAssoc(pos, dwSiteID, bnc);
    printf(buf, "insert placement_sitecat(ad_id,site_id,include) values(id,'%s',",
        adid, dwSiteID, includeList);
    if (!ifmain_exact(buf) || 1)
    {
        ASSERT(0);
    }
}
}

```

19-Jan-1996 15:58

AD.CPP

```

DOOL Ad::Book( DMORD advertId )
{
    char buf[1024];
    char startTime[10];

    if ( !advertId )
    {
        ASSERT( 0 );
        return( FALSE );
    }

    // If this is a barter ad, set max_impressions = 1
    if ( type == Barter )
    {
        maxImpressions = 1;
    }

    strcpy( buf, "insert placements(jumpto,max_impressions,type,ps,browser,domaintype,isp,freq,
    "img_ser,advertiser,flags,hours_of_day,days_of_week,employees,sales,descr,
    "max_amount,po_number,gender,active,approved,filename)" );

    if ( !startTime )
    {
        strcpy( buf, "start_time" );
    }

    if ( !endTime )
    {
        strcpy( buf, "end_time" );
    }

    strcpy( buf, "values" );

    addValue( buf, "jumpto" );
    addValue( buf, maxImpressions );
    addValue( buf, type );
    addValue( buf, "ps" );
    addValue( buf, browser );
    addValue( buf, domaintype );
    addValue( buf, isp );
    addValue( buf, frequency );
    addValue( buf, imgSer );
    addValue( buf, advertiser );
    addValue( buf, flags );
    addValue( buf, hoursOfDay );
    addValue( buf, daysOfWeek );
    addValue( buf, salesVolume );
    addValue( buf, nEmployee );
    addValue( buf, adDescription );
    addValue( buf, maxAmount );
    addValue( buf, poNumber );
    addValue( buf, gender );
    addValue( buf, active );
    addValue( buf, approved );
    addValue( buf, fileName, FALSE );

    if ( !startTime )
    {
        strcpy( buf, "start_time" );
        strcpy( buf, "end_time" );
        addValue( buf, startTime, FALSE );
    }

    if ( !endTime )
    {
        strcpy( buf, "start_time" );
        strcpy( buf, "end_time" );
        addValue( buf, endTime, FALSE );
    }

    if ( !main.enact( buf ) )
    {
        ASSERT( 0 );
        return( FALSE );
    }
}

```

HIGHLY
CONFIDENTIAL

DC 069518

19-Jan-1996 15:58

AD.CPP

```

// Get the ID of the newly added ad
int adID = 0;

{
    Cursor c;
    c.bind( SQL_C_LONG, adID, 4 );
    strcpy( buf, "select max(id) from placements" );
    c.exec( buf );
    c.fetchNext();
    if ( !main.commic() )
    {
        if ( !adID )
        {
            ASSERT( 0 );
            return( FALSE );
        }

        return( AddPlacementTable( adID ) );
    }

    DOOL Ad::Update();

    // To update an ad, we delete the existing ad
    // and re-book it.
    if ( !remove( FALSE ) )
    {
        // Determine if the ad is targeted
        double dPerAdCost = CalculateCostPerAd();
        if ( !dPerAdCost == BASE_AD_COST )
        {
            flags = Ad::Targeted;
        }
        else
        {
            flags = Ad::NotTargeted;
        }

        char buf[1024];
        char startTime[10];

        strcpy( buf, "update placements set " );

        // Don't update max_impressions if this is a barter ad. REP.EXE
        // Credits the placement so we don't want to overwrite the
        // barter credits
        if ( type != Barter )
        {
            strcpy( buf, "max_impressions=" );
            addValue( buf, maxImpressions );
        }

        strcpy( buf, "jumpto=" );
        addValue( buf, "jumpto" );
        strcpy( buf, "type=" );
        addValue( buf, type );
        strcpy( buf, "ps=" );
        addValue( buf, "ps" );
        strcpy( buf, "browser=" );
        addValue( buf, browser );
        strcpy( buf, "domaintype=" );
        addValue( buf, domaintype );
        strcpy( buf, "isp=" );
        addValue( buf, isp );
        strcpy( buf, "frequency=" );
        addValue( buf, frequency );
        strcpy( buf, "img_ser=" );
        addValue( buf, imgSer );
        strcpy( buf, "advertiser=" );
        addValue( buf, advertiser );
        strcpy( buf, "flags=" );
        addValue( buf, flags );
        strcpy( buf, "hours_of_day=" );
        addValue( buf, hoursOfDay );
        strcpy( buf, "days_of_week=" );
        addValue( buf, daysOfWeek );
        strcpy( buf, "employees=" );
        addValue( buf, nEmployee );
        strcpy( buf, "sales=" );
        addValue( buf, salesVolume );
        strcpy( buf, "ad_description=" );
        addValue( buf, adDescription );
        strcpy( buf, "max_amount=" );
        addValue( buf, maxAmount );
        strcpy( buf, "po_number=" );
        addValue( buf, poNumber );
        strcpy( buf, "gender=" );
        addValue( buf, gender );
        strcpy( buf, "active=" );
        addValue( buf, active );
        strcpy( buf, "approved=" );
        addValue( buf, approved );
        strcpy( buf, "filename=" );
        addValue( buf, fileName );

        if ( !startTime )
        {
            strcpy( buf, "start_time=" );
            if ( !startTime )
            {
                // ...
            }
        }
    }
}

```

```

ASSERT( 0 );
brc = FALSE;
break;

// Now save site page include-exclude list to the placement_sites table
pos = targetPages.GetStartPosition();
while (pos)
{
    targetPages.GetNextAssoc( pos, duPageID, bJunk );
    vprintf( buf, "insert placement_page(id, id, page_id, include values(id, id, id)",
        adID, duPageID, includePages );
    if ( !isMain.exec( buf ) )
    {
        ASSERT( 0 );
        brc = FALSE;
        break;
    }
    break;
}

// Remove from placement_sites
if ( !isMain.commit() )
    return( brc );

SQL Adl.Remove( SQL.RemoveFromPlacement );
char buf(1024);
SQL brc = TRUE;
while (TRUE)
{
    // Delete locations from the "placement_locations" table
    vprintf( buf, "delete placement_locations where ad_id=id", id );
    if ( !isMain.exec( buf ) )
    {
        ASSERT( 0 );
        brc = FALSE;
        break;
    }

    // Delete the site from the "placement_sites" table
    vprintf( buf, "delete placement_sites where ad_id=id", id );
    if ( !isMain.exec( buf ) )
    {
        ASSERT( 0 );
        brc = FALSE;
        break;
    }

    // Delete the site categories from the placement_sites table
    vprintf( buf, "delete placement_sites where ad_id=id", id );
    if ( !isMain.exec( buf ) )
    {
        ASSERT( 0 );
        brc = FALSE;
        break;
    }

    // Delete the user interests from the placement_interests table
}

```

DC 069520

HIGHLY
CONFIDENTIAL

```

// Delete placement_interests where ad_id=id, id
vprintf( buf, "delete placement_interests where ad_id=id", id );
if ( !isMain.exec( buf ) )
{
    ASSERT( 0 );
    brc = FALSE;
    break;
}

// Delete the site include-exclude list from the placement_sites table
vprintf( buf, "delete placement_sites where ad_id=id", id );
if ( !isMain.exec( buf ) )
{
    ASSERT( 0 );
    brc = FALSE;
    break;
}

// Delete the site page include-exclude list from the placement_sites table
vprintf( buf, "delete placement_pages where ad_id=id", id );
if ( !isMain.exec( buf ) )
{
    ASSERT( 0 );
    brc = FALSE;
    break;
}

// Remove from placement_sites
if ( !isMain.commit() )
    return( brc );

void Adl.Reset()
{
    dayOfWeek = 0;
    time = Production;
    frequency = 0;
    imageSeries = FALSE;
    multiImpressions = 0;
    type = Normal;
    domainType = 0;
    gender = 0;
    ageAmount = 0;
    ageNumber = Empty;
    startLine = 0;
    ending = 0;
    os = DefaultMask;
    browser = DefaultMask;
    domainType = DefaultMask;
    isp = DefaultMask;
    hourOfDay = DefaultMask;
    employees = DefaultMask;
    salesVolume = DefaultMask;
    gender = DefaultMask;
    includePages = 0;
    includeSites = 0;
}

```

```
seriesMapt = 0;  
delete () sicCodes;  
sicCodes = 0;  
sicCodes = NULL;  
delete () locations;  
locations = 0;  
locations = NULL;  
targetPages.RemoveAll();  
targetSites.RemoveAll();  
siteCategories.RemoveAll();  
interests.RemoveAll();  
adDescription.Empty();  
fileName.Empty();  
jumpTo.Empty();
```

Sendit

HIGHLY
CONFIDENTIAL

DC 069521